



STONEWALL™

Laminate Specifications



The strength of steel with the look of stacked stone.

When you want the authentic look of natural stacked stone with the strength and convenience of metal, STONEWALL™ Basement Egress Systems is your solution. This laminate product uses a 1 mil Polyethylene Terephthalate (PET) film designed to emulate the look of natural stone's durability and ruggedness.

St. Paul Corrugating Co., Inc.
 Email: info@stpaulcorrugating.com
 Web: stpaulcorrugating.com
 700 39th Ave NE
 Minneapolis MN 55421
 Toll free: 1-800-439-9271



Typical Test Results*

Performance	Test Method	Galvanized
Adhesion	ASTM D 3359	Less than 5%
Flexibility	ASTM D 4145	1T to 2T, no loss of adhesion
Pencil Hardness	ASTM D 3363	H Minimum
Reverse Impact	ASTM D 2794	3x metal thickness, NTO
Specular Gloss	ASTM D 523	Less than 30 at 60°
Salt Spray	ASTM D 117	1,000 hours - 1/2" max creep from scribe
Controlled Condensation	ASTM B 4585	1,000 hours - 8 F or better field blisters
Accelerated Outdoor Weathering	ASTM G 90	280MJ/m2 Chalk Rating no less than 10

*Results may vary depending on substrate and gauge