



# SPC Safe-T-View Covers™ Product Specification Information

## 1. PRODUCT NAME

Safe-T-View Cover™

2. MANUFACTURER  
St. Paul Corrugating Co.  
Minneapolis, MN 55421  
Phone: (763) 788-9271  
(800) 439-9271  
FAX: (763) 788-9273  
Email: info@stpaulcorrugating.com

## 3. PRODUCT DESCRIPTION

**Basic Use:** Designed to install over many manufacturers' window wells. Safe-T-View Covers™ unique vented design eliminates the greenhouse effect common in non-vented products. Hybrid galvanized frame with UV protected clear XL polycarbonate materials. You can see the strength™.

Innovative squeeze-and-size spring clip fastening installs on new and most retrofit applications. Clip adjustments can accommodate most window well distortion from irregular window well installations. Safe-T-View Covers™ has a sloped designed to aid drainage, eliminating standing water top of covers. Tested to 500 lbs, rated for 350 lbs. static load. Meets all specifications as provided by the IRC2006 egress code.


**Limitations:** Care should be used in proper installation of the Safe-T-View Covers™. Failure to mount the spring clips to the well and secure safety retainer-hinge lanyards may cause the cover to shift or blown off by the wind.

## 4. TECHNICAL DATA

**Covers:** Frames for Safe-T-View Covers™ are fabricated from 1" square inch galvanized steel tubes, welded as a back frame and supporting fingers. Clear UV protected polycarbonate, .118 thickness is riveted to supporting frame and secured with high bond foam adhesive tape. The polycarbonate is protected with a peelable protective film which should be removed at installation. Squeeze-and-size spring clips are adjustable and designed to clip over the window well rim. Safe-T-View Cover™ lanyards are mounted to each backbar and are designed to attach at the top bolts of the mounted window well. Tested to 500 lbs, rated for 350 lbs. static load.



Safety Retainer-Hinge



Squeeze-N-Size  
Adjustable Mounting

## Styles:




SV4236  
Fits span 39"-46"



SV5036  
Fits span 47"-54"

SV5536  
Fits span 53"-59"

SV6036  
Fits span 57"-64"



Safe-T-View Covers™ SV6736 or larger have a reinforced crossbar for added strength

SV6736  
Fits span 64"-71"

SV7536  
Fits span 72"-79"

SV8036  
Fits span 77"-84"

## 5. INSTALLATION

- Carefully un-wrap your new Safe-T-View Cover without the use of a box cutter (to ensure not damaging the XL polycarbonate). Please contact your local recycling center for responsible disposal of the cardboard packaging.
- Simply squeeze and size the pre-installed spring clips to the correct length and width dimensions for your installed areawall. Hand adjustments can be made as you lay the cover over the window well opening.
- Attach the safety retainer-hinge lanyards to the top bolts that mount the areawall to the foundation. \*Alternatively, anchor the loop end of the lanyard to the home foundation or directly to the areawall itself, depending on your particular application. Allow for enough lanyard length so the cover will pivot up and stay propped open against the side of the house.
- Peel back the protective film from the UV protected polycarbonate. Now stand back and take pleasure in the fact that in just minutes, you've installed the sturdiest, most innovative, and easiest to install cover product available today.

## 6. AVAILABILITY AND COST

Availability: Available through continental United States and Alaska through lumber yards and builder supply companies. Complete range of sizes available for shipment.

Cost: Varies by size and quantity. Freight allowance for qualifying orders.

## 7. WARRANTY

St Paul Corrugating, warrants Safe-T-View Covers™ ("Covers") window well cover to the original purchaser for a lifetime against breakage due to defects in materials or workmanship. For a period of ten (10) years from the date of purchase for excessive yellowing or discoloring of the XL polycarbonate, provided in each case that the Covers are used for their intended purposes only, and are maintained by the purchaser in accordance with the instructions provided with each cover.

## 8. MAINTENANCE

Check cover(s) regularly to see that it has not shifted or moved from its properly installed position. Covers should be kept clean to eliminate the build-up of hard water spots. Clean using a non-abrasive cloth with biodegradable soap and water. Hard water deposits can cause discoloration that is not covered under the warranty. Also inspect the cover to see if any parts are broken or missing. Any broken or missing parts should be repaired or replaced immediately. Please contact us for your replacement part needs.

St. Paul Corrugating Co, Inc.  
Email: info@stpaulcorrugating.com  
Web: stpaulcorrugating.com  
700 39th Ave NE  
Minneapolis MN 55421  
Toll free: 1-800-439-9271

